

Date :

2019/6/20



MORIMOTO Harness standard

品名	規格	直径(公差)	密度 intersection	荷重	構成	使用例	
Item name	m/roll *around1.0kg/roll	outside diamete (tolerance)	1cm density	sp tension	Composition of braid	Application example	
thin	MS-103	2100 m/roll	φ 0.70 ± 0.05	19.0 pcs	< 30 g	core 6 %	necktie, label
	MS-106CZ	2050 m/roll	φ 0.70 ± 0.05	19.0 pcs	< 30 g	core 6 %	necktie, homefabric, label
	MS-106	2000 m/roll	φ 0.75 ± 0.05	20.0 pcs	< 45 g	core 17 %	necktie, homefabric, label
	MS-203ZA	1700 m/roll	φ 0.80 ± 0.05	20.0 pcs	< 80 g	core 19 %	necktie, homefabric, label
	MS-205CZ	1500 m/roll	φ 0.85 ± 0.05	20.0 pcs	< 90 g	core 25 %	airbag, carseat, homefabric, needle, towel
	MS-205	1500 m/roll	φ 0.85 ± 0.05	20.0 pcs	< 100 g	core 25 %	airbag, carseat, homefabric, needle, towel
	MS-207	1200 m/roll	φ 0.95 ± 0.05	20.0 pcs	< 130 g	core 13 %	airbag, carseat, towel
	MS-209*	990 m/roll	φ 1.20 ± 0.05	20.0 pcs	< g	core %	
	MS-209	900 m/roll	φ 1.20 ± 0.05	20.0 pcs	< 150 g	core 10 %	towel, carpet, velvet
	MS-301	750 m/roll	φ 1.30 ± 0.05	18.0 pcs	< 150 g	core 13 %	carpet, velvet
	MS-303	650 m/roll	φ 1.40 ± 0.05	15.0 pcs	< 180 g	core 25 %	carpet, velvet
	MS-305	560 m/roll	φ 1.55 ± 0.05	15.0 pcs	< 180 g	core 28 %	carpet, velvet
	MS-403	450 m/roll	φ 1.85 ± 0.05	13.0 pcs	< 200 g	core 25 %	carpet, velvet
thick	MS-407	350 m/roll	φ 2.00 ± 0.05	11.0 pcs	< 250 g	core 19 %	carpet, velvet

CZ=Carbon in

*Without core

These Harness surfaces have an anti-static coating. It works better than carbon.